



EXTERIOR | INTERIOR
ZIRCONITE[®]
PROTECTION SYSTEM



Product Data Sheet

WHEEL CLEANER

User friendly and powerful clinging-gel wheel cleaner

- Specially formulated clinging-gel-foaming wheel cleaner
- For fast and efficient removal of burnt-on black break dust from lacquered alloy, painted steel and plastic wheel trims.
- Quickly removes road traffic film, dirt and oil to leave wheel surfaces clean, bright and shiny.
- Acid-free. Non-corrosive to skin
- Safe on plastic and tyres.

DIRECTIONS:

To activate; squeeze and lower red trigger lock.

Ensure wheels are cool. Do not apply in direct sunlight. Remove any loose dirt. Spray Wheel Cleaner directly onto the wheel, ensuring even coverage. Agitate with a wheel brush if required. Leave for 2-3 minutes to penetrate the dirt, up to a maximum of 10 minutes.

Do not allow cleaner to dry out or staining may occur.

Rinse thoroughly with a high pressure rinse, using clean water.

Caution: Anodised, un-lacquered or damaged wheels and trims may react adversely to any strong cleaning solution. If in doubt test a small area first. Do not use on stainless steel as staining will occur. Do not use on magnesium alloys, anodised alloys or un-lacquered alloy wheels or on any aircraft components.



ZIR510500
500ml/16.9fl/oz.

For additional information see relevant Safety Data Sheet.

Concept Chemicals & Coatings Ltd.
Windmill Lane Industrial Estate, Denton, Manchester, M34 3RB. ENGLAND. T: +44 (0)161 335 0213

Concept Chemicals EU Ltd.
The Gallery, 13 Bedford Row Limerick, V94 VY47 IRELAND



www.zirconitecoatings.com

CONCEPT